


E. Electronic Pressure Switches



E.1

hex 24
Performance
adjustable at factory

Electronic pressure switches, Performance series

hex 24, adjustable at factory



- Very attractively priced electronic pressure switches, particularly for high volume deployment
- High overpressure protection (up to 2 x)
- Small, compact electronic switches
- Broad diversity of electronic and mechanical connection options
- Ceramic sensor in thick film technology
- Monitoring of a pressure range due to window function
- Hysteresis adjustable within a wide range (2 % – 98 %, set at factory)
- High level of adaptability to your requirements (custom solutions)

Electronic pressure switches, Performance series

Technical details

Type:	0500 NO 0501 NC						
Transistor output:	PNP output (High-Side N-channel)						
Supply voltage:	9.6 – 32 VDC with reverse voltage protection						
Output current:	0.5 A with short-circuit and overvoltage protection						
Idle power consumption:	< 30 mA						
Adjustment range p_{nom} :	0 – 2 bar	0 – 4 bar	0 – 10 bar	0 – 16 bar	0 – 40 bar	0 – 100 bar	0 – 250 bar
Max. overpressure ¹⁾ :	4 bar	10 bar	20 bar	40 bar	100 bar	150 bar	375 bar
Burst pressure ¹⁾ :	8 bar	20 bar	35 bar	60 bar	140 bar	300 bar	500 bar
Mechanical life expectancy:	5,000,000 pulsations at rise rates to 1 bar/ms at p_{nom}						
Pressure rise:	≤ 1 bar/ms						
Accuracy:	±0.5 % of adjustment range p_{nom} (full scale (FS)) at room temperature						
Switching point adjustment range:	3 ... 100 % of adjustment range p_{nom} (FS), set at factory						
Hysteresis ²⁾ :	2 ... 98 % FS, programmable at factory (max. tolerance ±1.0% of adjustment range p_{nom})						
Default-Hysteresis without order specification:	2 bar	4 bar	10 bar	16 bar	40 bar	100 bar	250 bar
	0.1 bar	0.2 bar	0.5 bar	0.8 bar	2 bar	5 bar	10 bar
Operating mode:	with hysteresis or window function (see page 101), programmable at factory						
Resolution:	0.2 % of adjustment range p_{nom} (FS)						
Long term stability:	±0.1 % of adjustment range p_{nom} (FS) per year						
Repeatability ³⁾ :	±0.1 % of adjustment range p_{nom} (FS)						
Switching time:	< 4 ms						
Switch-on / -off delay:	Adjustable between 0 and 2 s (please specify when ordering, otherwise default 0 s is set)						
Temperature error ³⁾ :	±0.04 % of adjustment range p_{nom} (FS) / °C						
Compensated temperature range:	0 °C ... +70 °C (32 °F ... 158 °F), total error ≤ 2 %						
Temperature range ambient:	-30 °C ... +100 °C (-22 °F ... 212 °F)						
Temperature range media:	with TPE seal: -30 °C ... +110 °C (-22 °F ... +230 °F)						
	with NBR seal: -30 °C ... +100 °C (-22 °F ... +212 °F)						
	with EPDM seal: -30 °C ... +125 °C (-22 °F ... +257 °F)						
	with FKM seal: -20 °C ... +125 °C (-4 °F ... +257 °F)						
Wetted parts material	Housing:	Stainless steel (1.4305 / AISI 303)					
	Messuring cell:	Ceramic					
	Seal material:	TPE, NBR, EPDM or FKM					
Insulation resistance:	> 100 MΩ (500 VDC, $R_i > 42 \Omega$)						
Vibration resistance:	20 g; at 4...2000 Hz sine wave, DIN EN 60068-2-6						
Shock resistance:	500 m/s ² , 11 ms half sine wave; DIN EN 60068-2-27						
Protection class:	IP65: DIN EN 175301-803-A IP67: M12x1, AMP-Superseal®, cable connector IP67 and IP6K9K: Bayonet ISO 15170-A1-4.1, Deutsch DT04-3P						
Electromagnetic compatibility:	EMV 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007						
Cable output thread size:	For DIN EN 175301: Pg9 (outside diameter of cable 6 to 9 mm)						
Weight:	approx. 80 g (DIN EN 175301 approx. 110 g)						

¹⁾ Static pressure, dynamic pressure 30 to 50 % lower. Values refer to the hydraulic or pneumatic part of the electronic pressure switch.

²⁾ 3 ... 98 % with programming device PPD05 (see page 133).

³⁾ Within the compensated temperature range.



E.1

hex 24
Performance
adjustable at factory

0500 / 0501

Electrical connectors and threads



hex 24

	NO / NC
○ 1	(Uv+)
○ 2	(Gnd)
○ 3	(U _{out})

DIN EN 17530-803-A

Pin	Assignment
1	Uv+
2	Gnd
3	U _{out}
PE	

IP65

x ~ 60 mm without coupler socket
x ~ 77 mm with coupler socket

Order number: 013

M12 – DIN EN 61076-2-101 A

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	U _{out}

IP67

x ~ 54 mm

Order number: 002

ISO 15170-A1-4.1

Pin	Assignment
1	Uv+
2	Gnd
3	U _{out}
4	nc

IP67, IP6K9K

x ~ 56 mm

Order number: 004

AMP Superseal 1.5®

Pin	Assignment
1	U _{out}
2	Gnd
3	Uv+

IP67

x ~ 61 mm

Order number: 007

Deutsch DT04-3P

Pin	Assignment
A	Uv+
B	Gnd
C	U _{out}

IP67, IP6K9K

x ~ 61 mm

Order number: 010

Cable connection

Pin	Assignment
red	Uv+
white	U _{out}
black	Gnd

IP67

x ~ 47 mm
(+ 25 mm bend relief)
Cable length ~ 2 m

Order number: 011

G 1/4 DIN
EN ISO 1179-2
(DIN 3852-11)
form E

Sealing ring

Thread code: 41

NPT 1/4

Thread code: 09



0500 / 0501

Order matrix for electronic pressure switches

E.1

hex 24
Performance
adjustable at factory



	Type	Adjustment range	Pressure connection	Seal material	Electrical connection
--	------	------------------	---------------------	---------------	-----------------------

Type

Normally open (NO), PNP, switching points programmed at factory ¹⁾	0500
Normally closed (NC), PNP, switching points programmed at factory ¹⁾	0501

Max. overpressure ²⁾	Burst pressure	Adjustment range ¹⁾	
4 bar	8 bar	0 - 2 bar (approx. 29 PSI)	200
10 bar	20 bar	0 - 4 bar (approx. 58 PSI)	400
20 bar	35 bar	0 - 10 bar (approx. 145 PSI)	101
40 bar	60 bar	0 - 16 bar (approx. 230 PSI)	161
100 bar	140 bar	0 - 40 bar (approx. 580 PSI)	401
150 bar	300 bar	0 - 100 bar (approx. 1,450 PSI)	102
375 bar	500 bar	0 - 250 bar (approx. 3,625 PSI)	252

Pressure connection

G 1/4 – DIN EN ISO 1179-2 (DIN 3852-11), form E	41
NPT 1/4	09

Seal material – Application areas

NBR	Hydraulic/machine oil, heating oil, air, nitrogen, etc.	1
EPDM	Brake fluid, water, acetylene, hydrogen etc.	2
FKM	Hydraulic fluids (HFA, HFB, HFD), petrol/gasoline etc.	3
TPE	Hydraulic/machine oil, air, nitrogen, water, acetylene etc.	7

Electrical connection

DIN EN 175301-803-A (DIN 43650-A); socket device included	013
M 12x1 - DIN EN 61076-2-101-A	002
Bayonet ISO 15170-A1-4.1 (DIN 72585-A1-4.1)	004
AMP Superseal 1.5°	007
Deutsch DT04-3P	010
Cable connection (length of cable 2 m standard)	011

Order number:	05XX	XXX	XX	X	XXX
----------------------	------	-----	----	---	-----

¹⁾ Please state switching point and hysteresis when ordering.

²⁾ Static pressure, dynamic pressure 30 to 50 % lower. Values refer to the hydraulic or pneumatic part of the electronic pressure switch.

